














Assembly kits for double walled pipeworks:

Artikelnr. Part.No.	Description	Material	
42001160	<p>Assembly kit for leak detector type D25, D26, D29 connected to: - double walled pipes</p> <p>Consist of:</p> <ul style="list-style-type: none"> - 1 pc pressure connector - 1 pc test valve unit - connectors: pipe 1/4 inch, - for D29: connect pressure line with measuring line via separate t-connector outside tubing diameter 6 mm - material: brass 	Brass	
42001060	<p>Assembly kit for leak detector type D25, D26, D29, connected to: - double walled pipes</p> <p>Consist of:</p> <ul style="list-style-type: none"> - 1 pc pressure connector - 1 pc test valve unit - connectors: pipe 1 inch, - for D29: connect pressure line with measuring line via separate t-connector outside tubing diameter 6 mm - material: brass 	Brass	
42001320	<p>Assembly kit for leak detector type D25, D26, connected to: - double walled pipes</p> <p>Consist of:</p> <ul style="list-style-type: none"> - 1 pc pressure connector - 1 pc test valve unit - connectors: pipe 1/4 inch, outside tubing diameter 6 mm <p>Material: stainless steel</p>	Stainless steel	
42001282	<p>Manifold kit for leak detector type D25 / D26, connected to: - 2 double walled pipes</p> <p>Consists of:</p> <ul style="list-style-type: none"> - 2 pcs. ball valves - 2 pcs. Manometer 25 bar - Connectors for 6 mm outside tubing diameter 	Brass	
42001283	<p>Manifold kit for leak detector type D25 / D26, connected to: - 3 double walled pipes</p> <p>Consists of:</p> <ul style="list-style-type: none"> - 3 pcs. ball valves - 3 pcs. Manometer 25 bar - Connectors for 6 mm outside tubing diameter 	Brass	
42001284	<p>Manifold kit for leak detector type D25 / D26, connected to: - 4 double walled pipes</p> <p>Consists of:</p> <ul style="list-style-type: none"> - 4 pcs. ball valves - 4 pcs. Manometer 25 bar - Connectors for 6 mm outside tubing diameter 	Brass	
42001285	<p>Manifold kit for leak detector type D25 / D26, connected to: - 5 double walled pipes</p> <p>Consists of:</p> <ul style="list-style-type: none"> - 5 pcs. ball valves - 5 pcs. Manometer 25 bar - Connectors for 6 mm outside tubing diameter 	Brass	





Assembly kits for double walled pipeworks:

Artikelnr. Part.No.	Description	Material	
42001286	Manifold kit for leak detector type D25 / D26 , connected to: - 6 double walled pipes Consists of: - 6 pcs. ball valves - 6 pcs. Manometer 25 bar - Connectors for 6 mm outside tubing diameter	Brass	
42001287	Manifold kit for leak detector type D25 / D26 , connected to: - 7 double walled pipes Consists of: - 7 pcs. ball valves - 7 pcs. Manometer 25 bar - Connectors for 6 mm outside tubing diameter	Brass	
42001288	Manifold kit for leak detector type D25 / D26 , connected to: - 8 double walled pipes Consists of: - 8 pcs. ball valves - 8 pcs. Manometer 25 bar - Connectors for 6 mm outside tubing diameter	Brass	
42007009	Filling- and test armature for leak detector type D25, D10 for connection to the quick connector of the leak detector consisting of - gauge 25bar - connector 1/4" for pressure reducing valve - pressure Hose - connector plug - 2pc ball valves for filling and draining	Brass	
42007007	Test armature for leak detector type D26, D11 for connection to the quick connector of the leak detector, consisting of - gauge 25bar - pressure Hose - connector plug	Brass	
49307034	Gauge 0-25 bar for leak detector type D25 and D26 for assembly to the leak detector into the measuring line - connectors for 6 mm (outside tubingØ) - material brass	Brass	
49307044	Gauge 0-10 bar for leak detector type D25 and D26 2/4 and 2/6 bar - for assembly to the leak detector into the measuring line - connectors for 6 mm (outside tubingØ) - material brass	Brass	

Assembly kits for double walled pipeworks:

Artikelnr. Part.No.	Description	Material	
42001161	Assembly kit for leak detector type D29 , connected to: - double walled pipes Consist of: - 2 pcs connectors (pressure and measuring line) - 1 pc test valve unit - connectors: pipe 1/4 inch , outside tubing diameter 6 mm	Brass	
42003578	Air dryer (external) for leakdetector type D9, D29, 180ccm , with mounting angle, connectors for 4mm (inside hoseØ), without dry beads	Plastics	Ref. Nr. 42003578 180 cm ³ , LTR 3 
42003589	Air dryer (external) for leakdetector type D9, D29, 350ccm , with mounting angle, connectors for 4mm (inside hoseØ), without dry beads	Plastics	Ref. Nr. 42003589 350 cm ³ , LTR 4 
42003591	Air dryer (external) for leakdetector type D9, D29, 550ccm , with mounting angle, connectors for 4mm (inside hoseØ), without dry beads	Plastics	Ref. Nr. 42003591 550 cm ³ , LTR 6 
42006001	Assembly kit for leak detector type V8 for assembly to double walled pipes consisting of - tank connection 1/4" - 1x liquid barrier in suction line - T-fitting to measuring line - connectors for 6mm (outside tubingØ) - ball valve at the end of the pipe - Material brass	Brass	
42006003	Assembly kit for leak detector type V80Ex, V90 for assembly to double walled pipes consisting of - flame arrester explosion group IIA temperature class T4 - 1pc liquid barrier in suction line - T-fitting to measuring line - connectors: pipe 1/4" - connectors for 6 mm (outside tubingØ) - Ball connector at the end of the pipe - material brass	Brass	

Assembly kits for double walled pipeworks:

Artikelnr. Part.No.	Description	Material	
42006002	Assembly kit exhaustline to assamble to an vacuum leakdetector in case exhaust line can not be lead back to the tank consisting of -1pc liquid barrier -water trap -mounting angle -connection lines for 6 mm outside diameter - Material brass	Brass	
42006004	Assembly kit for leak detector type V80Ex V90 for assembly to double walled pipes consisting of - flame arrestor explosion group IIA temperature class T4 - 1pc liquid barrier in suction line - T-fitting to mearusing line - connectors: pipe 1/4" - connectors for 6 mm (outside tubingØ) - Ball conector at the end of the pipe - material stainless steel	Stainless steel	
42006006	Assembly kit for leak detector type V80Ex for assembly to double walled pipes consisting of - flame arrestor explosion group IIB3 temperature class T4 - 1pc liquid barrier in suction line - T-fitting to mearusing line - connectors: pipe 1/4" - connectors for 6 mm (outside tubingØ) - ball conector at the end of the pipe - material stainless steel	Stainless steel	
42006005	Assembly kit exhaustline to assamble to an vacuum leakdetector in case exhaust line can not be lead back to the tank consisting of - 1pc liquid barrier - water trap - mounting angle - connectors for 6 mm (outside tubingØ) - material stainless steel	Stainless steel	
49302901	Liquid barrier for leak detector type V80ExVA, V90VA, V33 -1/4" female screw thread -3/4"external screw thread - meterial stainless steel	Stainless steel	